





The mobile multifunctional set consisting of a Trigger Handle (hand-held barcode scanner) and an industrial smartphone IS530.x is a flexible combination for reliable data acquisition in Ex areas. The HID-active, ready-to-use high-performance scanner captures any 1D or 2D barcodes at close range of up to 6 meters or distances of up to 18 meters via the reliable Zebra OEM imager scan engines. The data is further processed directly via the IS530.x smartphone connected via the ISM interface.

> All trademarks and copyrights are the properties of their respective owners. > © 2022 by i.safe MOBILE GmbH | All rights reserved. | Misprints, errors and modifications excepted. | 1040MD01REV13_EN_06.2022





ATEX approval: Ex-Zone 1/21 ll 2G Ex ib op is IIC T4 Gb ll 2D Ex ib op is IIIC T135°C Db



IECEx approval: Ex-Zone 1/21 Ex ib op is IIC T4 Gb Ex ib op is IIIC T135°C Db



NEC500 approval: Class I Division 1, Groups A B C D T4 Class II Division 1, Groups E F G T135°C Class III Division 1

Further approvals: JNIOSH (Japan)

| TECHNICAL FEATURES | |
|---------------------|---|
| Weight | MR = 380 g ER = 400 g (without IS530) |
| Size | 202 x 90,4 x 125 mm |
| Indication function | Loudspeaker Vibration LED-Display |
| Power supply | Over IS530 this can be loaded in the handle |
| Communication | Over the multi functional ISM interface of the IS530 |
| Type of protection | MIL-STD 810H IP68 dust-/waterproof usable from -20 °C to +60 °C |

SCAN TYPES

IS-TH1MR.1 (mid range) with Zebra SE4750 MR | up to 6 m

IS-TH1ER.1 (extended range) with **Zebra SE4850 ER** | up to 18 m



2,4 GHz + 5 GHz: IEEE 802.11 a/b/g/n/ac/e/k/r/h with hotspot for max. 8 connections 4,5" Gorilla Glass® 3. generation, resolution 854 x 480 pixels

GSM 850/900/1800/ 1900 MHz WCDMA: UMTS B1/2/4/5/8 LTE-FDD: B1/2/3/4/5/7/8/12 with MFBI B13/14/17/20/25/ 26/28A/28B/29/30/66 LTE-TDD: B38/B39/B40/B41 TD-SCDMA: B34/B39



Qualcomm Snapdragon SDM660 Octa-Core Kryo Gold-Quad cores 2,2 GHz Kryo Silver-Quad cores 1,8 GHz 4 GB RAM 64 GB internal memory

3600 mAh battery,

replaceable,

3.8 V. 13.68 Wh

The complete description you will find on our homepage: www.isafe-mobile.com

Please visit our website and you will find more detailed information, as well as an overview of compatible accessories.